

DIN-Tabelle Kugellager zweireihig

Standard-Lieferprogramm

info@hakuparts.com

Bezeichnung (DIN 625)	Außen-Ø in mm	Innen-Ø in mm	Breite in mm	Tragfähigkeit		
				stat N	dyn N	n max. U/min
623	10	3	6	45	81	4050
624	13	4	8	72	108	3250
625	16	5	9	81	117	2750
626	19	6	10	90	126	2340
607	19	7	10	90	126	2340
627	22	7	10	99	144	1980
608	22	8	10	99	144	1980
609	24	9	10	108	162	1850
629	26	9	13	126	180	1710
6000	26	10	13	162	234	1710
6200	30	10	13	198	288	1480
6300	35	10	18	342	504	1260
6001	28	12	13	198	288	1580
6201	32	12	16	270	396	1390
6301	37	12	20	378	558	1170
16002	32	15	13	234	342	1350
6002	32	15	13	252	360	1350
6202	35	15	16	306	450	1260
6302	42	15	20	468	666	1080
16003	35	17	13	288	432	1260
6003	35	17	13	306	468	1260
6203	40	17	18	396	576	1120
6303	47	17	20	468	666	945
16004	42	20	16	342	522	1035
6004	42	20	16	360	540	1035
6204	47	20	20	486	756	945
6304	52	20	25	630	900	855
16005	47	25	16	378	558	950
6005	47	25	17	432	648	950
6205	52	25	20	576	864	855
6305	62	25	30	720	1080	650
16006	55	30	17	432	666	810
6006	55	30	18	504	756	810
6206	62	30	24	648	990	720
6306	72	30	32	828	1260	600
16007	62	35	17	432	666	720
6007	62	35	20	576	864	720
6207	72	35	28	738	1116	630
6307	80	35	35	882	1350	540
16008	68	40	17	540	810	675
6008	68	40	22	630	936	675
6208	80	40	32	792	1188	560
6308	90	40	36	936	1440	510
16009	75	45	18	594	900	575
6009	75	45	23	684	1008	575
6209	85	45	32	846	1296	520
6309	100	45	40	972	1620	500
6010	80	50	26	702	1044	540
6210	90	50	32	972	1386	500
6011	90	55	28	720	1080	480
6211	100	55	38	1080	1440	450
6012	95	60	28	756	1152	450

